

Hardware By Others

Preparation Only By Tubelite

Hardware. An approved hardware schedule and all customer furnished hardware which requires Tubelite preparation and/or installation must be received by Tubelite prior to preparation of fabrication documents and release to production. Expediting hardware by others will be the responsibility of the Buyer. Door hardware furnished by others must be shipped prepaid to Tubelite with a detailed packing list, and marked with the following information:

Tubelite Factory Order Number Customer's Name & Address
 Project Name & Location Door Numbers marked on each hardware item

Any deviation from the packing list to the actual contents of hardware received is the responsibility of the Buyer. Tubelite makes no representation with regard to the suitability, adequacy or compliance to the approved hardware schedule when hardware is supplied by others. Tubelite's delivery schedule may be extended due to inadequate coordination or late delivery of hardware by others. Hardware received without the required information will be returned freight collect to the Buyer.

Hinge Swage: In order to maintain the standard Tubelite clearances in door openings all hinges supplied by others are required to have Zero swaging. All hinges received by Tubelite requiring swage adjustment will be charged accordingly. A handling charge will be applied to all hardware (such as surface closers, thresholds, and floor checks) received, but not required or requested by Tubelite.

Note: Make sure all hardware will work with 2" thick doors.

Hardware	Hardware Description	Preparation To:				
				Door	*Frame	
Hinges	Butts – mortised (round corners) Tubelite standard door opening clearance requires zero hinge swage. Charge to swage hinges by others.	Each	BHPD	\$ 67	BHPF	\$ 67
		Each	BHSWAGE	\$ 18		
	Continuous Gear Hinge	Each	CGHPD	\$ 93	CGHPF	\$ 93
Pivots	OFFSET:					
	Top offset pivots	Each	OPTPD	\$ 57	OPTPF	\$ 57
	Bottom offset pivot	Each	OPBPD	\$ 57	OPBPF	\$ 57
	Intermediate offset pivot	Each	OIPD	\$ 75	OIPF	\$ 75
	CENTER HUNG:					
	Top center pivot	Each	CPTPD	\$ 93	CPTPF	\$ 93
	Bottom center pivot	Each	CPBPD	\$ 93	CPBPF	\$ 93
Locks	Mortised Deadlock	Each	MDLPD	\$ 337	MDLPF	\$ 38
	Cylindrical/Knob Lock	Each	CKLPD	\$ 337	CKLPF	\$ 38
	May require 5" Wide Stile					
 HOLDERS	OVERHEAD TYPE:					
	Surface mounted overhead holder	Each	SOHHPD	\$ 75	SOHHPF	\$ 75
	Concealed mounted overhead holder	Each	COHHPD	\$ 95	COHHPF	\$ 75

*Charge applies to frame or to meeting rail of double doors as required.

Hardware By Others

Preparation Only By Tubelite

Hardware. An approved hardware schedule and all customer furnished hardware which requires Tubelite preparation and/or installation must be received by Tubelite prior to preparation of fabrication documents and release to production. Expediting hardware by others will be the responsibility of the Buyer. Door hardware furnished by others must be shipped prepaid to Tubelite with a detailed packing list, and marked with the following information:

Tubelite Factory Order Number Customer's Name & Address
 Project Name & Location Door Numbers marked on each hardware item

Any deviation from the packing list to the actual contents of hardware received is the responsibility of the Buyer. Tubelite makes no representation with regard to the suitability, adequacy or compliance to the approved hardware schedule when hardware is supplied by others. Tubelite's delivery schedule may be extended due to inadequate coordination or late delivery of hardware by others. Hardware received without the required information will be returned freight collect to the Buyer.

Hinge Swage: In order to maintain the standard Tubelite clearances in door openings all hinges supplied by others are required to have Zero swaging. All hinges received by Tubelite requiring swage adjustment will be charged accordingly. A handling charge will be applied to all hardware (such as surface closers, thresholds, and floor checks) received, but not required or requested by Tubelite.

Note: Make sure all hardware will work with 2" thick doors.

Hardware	Hardware Description	Preparation To:				
		Door		*Frame		
Closers	Closers - overhead concealed (Price includes preparation for top arm and frame preparation for closer. Add price for pivot or hinge preparation.)	Each	OHCCPD	\$ 55	OHCCPF	\$ 115
	Closers - floor type - all makes (Price includes preparation for bottom arm. Add price for appropriate top pivots.)					
	Offset pivots	Each	FCOPPD	\$ 93	FCOPPF	\$ 67
	Center pivots	Each	FCCPPD	\$ 93	FCCPPF	\$ 93
Panics	Panic Device - concealed vertical rod	Each	CVRPD	\$ 300	CVRPF	\$ 100
	Panic Device - rim type	Each	RIMPD	\$ 170	RIMPF	\$ 40
	Panic Device - mortised type	Each	MPPD	\$ 300	MPPF	\$ 100
Kick Plates	Kick Plates - one side only - up to 12" high	Each	KPPD	\$ 90	-	-
Push-Pulls	Push Bar - Surface mounted	Each	PBPD	\$ 15	-	-
	Pull Handle - Surface mounted	Each	PHPD	\$ 30	-	-
Miscellaneous	Electric Releases (strikes) all makes	Each	-	-	ERPF	\$ 112
	Inactive Leaf on Pairs	Each	ERPDP	\$ 115	-	-
	Flush Bolts - all makes	Per Pair	FBPD	\$ 40	FBPF	\$ 20

*Charge applies to frame or to meeting rail of double doors as required.